

Application Serial No. 10/534,927  
 Reply to Office Action of January 24, 2006

PATENT  
 Docket: CU-4209

### Amendments to the Claims

The listing of claims presented below replaces all prior versions, and listings, of claims in the application.

#### Listing of claims:

1. (currently amended) Equipment for change of rotary gobos comprising a carrier disc provided with circular apertures ~~[[ (9) ]]~~ allowing for lighting of gobos and furnished with ~~resilient holding means~~ a holder to support interchangeable segments with the gobos, ~~characterised in, that wherein~~ each segment ~~[[ (2) ]]~~ is provided with a lamella ~~[[ (3) ]]~~ for attachment in the ~~holding means~~ holder and with ~~means for a setting portion to position~~ the segment ~~[[ (2) ]]~~ on the carrier disc ~~[[ (1) ]]~~.
2. (currently amended) Equipment for a change of rotary gobos according to claim 1, ~~characterised in, that wherein~~ the ~~holding means comprise~~ holder comprises a system of flexible fingers ~~[[ (10) ]]~~ In a fan-shaped arrangement, the fingers ~~[[ (10) ]]~~ being at inside ends fixed to the carrier disc ~~[[ (1) ]]~~, and on the outside free ends is adapted to allow for insertion of the segment lamellas ~~[[ (3) ]]~~ between the fingers ~~[[ (10) ]]~~ and the carrier disc ~~[[ (1) ]]~~.
3. (currently amended) Equipment for a change of rotary gobos according to claim 2, ~~characterised in, that wherein~~ inside ends of the fingers ~~[[ (10) ]]~~ are at their inside ends integrated into one unit, while the number of fingers ~~[[ (10) ]]~~ within this unit corresponds to the number of segments ~~[[ (2) ]]~~ to be supported by the carrier disc ~~[[ (1) ]]~~.
4. (currently amended) Equipment for a change of rotary gobos according to claim 1, ~~characterised in, that wherein~~ each segment ~~[[ (2) ]]~~ is provided with a bearing supporting a driver ~~[[ (6) ]]~~ with a gobo, ~~[[ the ]]~~ wherein a bearing inside ring being is provided ~~[[ for ]]~~ by ~~[[ the ]]~~ a driver ~~[[ (6) ]]~~ outer rim, and ~~[[ the ]]~~ a bearing outside ring ~~(5)~~ being is attached to the segment lamella ~~[[ (3) ]]~~ by a dismountable-connection means, while the driver ~~(6)~~ comprise comprises a flange ~~[[ (7) ]]~~ with a spur toothing.

Application Serial No. 10/534,927  
Reply to Office Action of January 24, 2006

PATENT  
Docket: CU-4209

5. (currently amended) Equipment for a change of rotary gobos according to claim 1 or 4, ~~characterized in, that~~ wherein the ~~means for setting portion for positioning~~ the segment ~~[[ (2) ]]~~ on the carrier disc ~~(1) comprise~~ comprises a dismountable-connection ~~means~~ for attachment of the gobo bearing outer ring ~~[[ (5) ]]~~ on the lamella ~~[[ (3) ]]~~.